

Rasco Bitumen Primer Concentrate

Solvent-free, water-dilutable primer based on bitumen emulsion for use with all **Rasco bitumen thick coatings**

It can be applied to vertical and horizontal surfaces, foundation slabs, foundations and cellar walls. Can be used on all known and suitable mineral substrates as well as old pre-treated bituminous paints and thick coatings.



PRODUCT FEATURES

- Solvent-free and environmentally friendly
- Easy processing
- Rapid drying
- Applicable with brush or roll
- When diluted with water (1:10) suitable for all **Rasco Bitumen thick coatings**
- Frost-free at least 12 months shelf-life

TECHNICAL DATA

Consumption*	0.1-0.2 kg/m ²
Density	approx. 1.1 kg/l
Drying time**	45-60 minutes
Mixing ratio	1:10 (Primer:Water)
Working and drying temperature***	+5°C to +30°C

* The consumption rates shown are minimum values. These may increase according to the manner of application.

** These times may vary greatly, depending on humidity, temperature, coating thickness and substrate. Times are based on the standard climate of + 23 °C and 50 % relative humidity.

*** Temperature: component, installation and ambient temperature.

DELIVERY UNITS

30 kg bucket | 18 buckets / pallet | pallet weight approx. 580 kg

10 kg bucket | 44 buckets / pallet | pallet weight approx. 480 kg

5 kg bucket | 80 buckets / pallet | pallet weight approx. 440 kg

GENERAL NOTES

In case of sealing or maintenance work the relevant standards and guidelines must be followed.

SUBSTRATE PREPARATION

- The substrate must be sufficiently dry, level, stable, frost-protected, clean and without traces of oil, grease, tar, honeycombing, cracks, dust, dirt, residue mortar or other potential contaminants.
- Edges should be broken and inside joints rounded out with suitable material.

APPLICATION

- Mix **Rasco Bitumen Primer Concentrate** with water according to the mixing ratio advised and apply with a wide brush, brush, roll or suitable spraying technique evenly to the prepared substrate.

SPECIAL NOTES

- Protect the newly applied primer from rain, frost and strong sun light until completely dry.
- Further information regarding **Rasco bitumen thick coatings** and other systemic products may be found on our website <http://www.rasco-bitumen.com/>.
- Please note the Safety Data Sheet (accessible at <http://www.rasco-bitumen.com/>)

Note: The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the Rasco product installation. For the most up-to-date TDS and warranty information, please visit our website at www.rasco-bitumen.com. Any alterations to the wording or requirements contained in or derived from this TDS shall void all related Rasco warranties.

Issue 04: This document has been updated with respect to the release of the new waterproofing standard DIN 18533. When this version is updated it will lose its validity.